Flight 60T Tech Specs

Ventilator designed to provide Invasive and Non-Invasive ventilation for the critical care management of adult and pediatric patients greater than 5 kg

Modes of Venti	lation			
 Spont 	(CPAF	P/BiPAP/BiPAP ST/PSV)		
 ACMV 	(Press	sure control/Volume control/PRVC)		
 SIMV 	(Press	sure control/Volume control/PRVC)		
 B-Lev 	(Bi-Le	vel, APRV, Bi-Phasic, Duo-PAP)		
 Volume Guara 	antee VtG 8	MVG (VG PS/ AVAPS)		
 NIV leak comp 	ensation Up to	100 l/min		
 HFOT* 	(High	Flow Oxygen Therapy)		
Operating Env	ironment			
 Temperature 		to 50°C / -4°F to 122°F		
Humidity		o 95% at 31° C/88° F		
Altitude:		a to 110KPa		
Storage T°		to 71°C / -4°F to 160°F		
Water/Dust Re		Splash Proof)		
Dimensions		,		
Width	29 cm	/11.4"		
Height		/9.8"		
Depth		1/11.0"		
Weight		7 / 6 kg with integrated mixer		
User Interface	3.3 1(8	// o kg with integrated mixer		
	color I CD touchs	croon		
7" easy to use color LCD touchscreenLanguages: English, German, French, Italian, Spanish, Portuguese,				
		ek, Turkish, Japanese, Chinese		
Adjustable bu		ek, Turkisii, Japanese, Cilinese		
5 preset customizable settings Lockable keypad buttons				
Power SourcesAC		240V, 50-60Hz		
• AC	100 to			
Power Save		ff/Night		
	le batteries Up to			
	ie butteries op to	0 110 013		
 Controls Flow: Up to 220 l/min (internal mixer) / 150 l/min (external mixer) 				
 Flow: Up to 2 Tidal Volume 		2,200 ml		
Breath Rate		9 BPM		
Manual Breat				
Pressure Con		0 cmH ₂ O		
Volume Conti				
Pressure Sup		0 cmH ₂ O		
 PSV flow term 		0 90%		
PEEP/CPAP		0 cmH ₂ O		
Pressure Trigg		-0.1 cmH ₂ O		
Flow Trigger		0 l/min		
Rise Profile	5 leve	•		
Inspiratory Ti				
HFOT Flow		60 LPM		
• FiO ₂		o 100%		
• 2 min 100% C				
- Z 111111 100% C	2 actively			

	igh	On/Off
Sy	nchronized nebulizer*	5 to 60 min
	aneuvers	
	titude compensation	Off, 500 to 4,500 m
	utomatic Purge circuit	60 to 300 sec
• C	ustomizable Apnea Ventilation	
B-Le	ev Controls (APRV)	
• T	high	1 to 15 sec
• T	low	0.5 to 5 sec
• P	high	3 to 60 cmH ₂ O
• P	low	0 to 40 cmH ₂ O
• In	iverse I:E	30:1
Alar	ms	
	arm prioritization	3 levels - Caution/Medium/High
	pnea	10 to 60 sec
	attery	Low/Empty/Disconnection
• L(ow/High Minute Volume	
• L(ow/High Pressure	
• Lo	ow/High FiO ₂	
• Lo	ow Vti/Vte	
• C	heck patient circuit	
• 0	₂ sensor defective	
• 0	₂ supply failed	
• L	ow/High Breath Rate	
Mon	itors	
 A 	irway pressure LED Gauge	-10 to 120 cmH ₂ O
 Per 	eak Inspiratory Pressure (PIP)	0 to 120 cmH ₂ O
• In	haled/ Exhaled Tidal Volume	0 to 10 L
 In 	haled/ Exhaled Minute Volume	0 to 99 l/min
 B 	ase / Mean Pressure	0 to 99 cmH ₂ O
 A 	ctual breath rate	0 to 99 BPM
• Fi	02	21% to 100%
• :	E Ratio	1:99 to 3:1
 R: 	SBI	0 to 200 1/min x l
• W	'aveforms	Pressure, Flow, Volume
• L	oops	Pressure vs Volume, Flow vs Volume
• Tı	rends	Breath rate, PIP, Vte (up to 72 hours
• Lu	ung mechanics	P Plateau, Static compliance
Оху	gen	
	ptional O ₂ mixer	Internal electronically controlled
• H	igh Pressure/Low Flow Port	35 to 90 psi / 0 to 15 l/min
	ompatible with oxygen tanks and	
Con	nmunication	
	USB ports	Download logs, SW upgrade
	external RS232 connectors	Remote Alarm and Monitoring
	J 45 connector	
	ndards	
	C 60601-1, IEC 60601-1-2, IEC 606	01_2_12 ISO 10651 2/2
- IL		01 2 12, 130 10031-2/3,

*HFOT and Nebulizer are not available in USA *HFOT is available from SW version 5.33 and up



FDA cleared



Flight 60T®

Reliable Ventilation Across the Spectrum of Care



Flight Medical Innovations Ltd. manufactures, develops and markets life supporting respiratory ventilators for critical care and emergency environments, long term acute care facilities, homecare, transport, military, mass casualty and emergency preparedness.

Flight 60T®

The Flight 60T is a fully independent, turbine-based, ventilator.

The worldwide deployed Flight 60T is both a volume-control and pressure-control ventilator for invasive and noninvasive ventilation, and also offers High Flow Oxygen Therapy (HFOT).

Cost effective, value driven solution for reliable ventilation, across the spectrum of care.



- Adults and pediatric patients greater than 5 kg
- Pressure and volume control ventilation

in all clinical situations

- Basic and advanced modes
- Non-invasive and invasive ventilation
- ICU modes: B-Lev, PRVC, Volume Guarantee
- Continuous monitoring of breathing parameters
- Flow or Pressure Trigger for optimum patient-machine synchrony
- Internal Mixer: Low flow and high pressure 0₂, 100% 0₂ preset
- Customized apnea backup ventilation to keep patients' parameters
- Extensive alarms system
- Does not require connection to air inlet
- Lung mechanics

- Invasive and non-invasive ventilation
- The Flight 60T provides the tools needed to effectively ventilate your patients in any care environment
- The Flight 60T offers advanced weaning modes, preset quick ventilation options
- The Flight 60T's portability, along with long battery life, is the perfect solution when it comes to providing powerful ventilation
- Low flow oxygen inlet, no need to have high pressure oxygen source
- Splash-proof: Allows the patient to leave the ventilator near the shower
- Lockable screen to avoid any unattended action
- Ability to dim visual screen for night time patient comfort
- · Mouthpiece ventilation capabilities

• Automatic leak compensation allows for effective and comfortable mask ventilation in a wide range of modes

switch devices

- Pressure support in CPAP and BiPAP modes to provide ideal assistance
- Both Flow and Pressure Trigger options
- When moving between invasive and non-invasive therapies utilize the same equipment and same patient circuit
- · Integrated and compensated nebulizer (Not available in USA)
- High Flow Oxygen Therapy (HFOT) provides non-invasive respiratory support that improves oxygenation while also reducing work of breathing (not available in USA)
- Whether it is critical care transport outside the hospital, emergency preparedness or mass casualty response, the Flight 60 provides a sturdy and reliable solution for all levels of required ventilation. Its autonomous platform allows caregivers to treat patients in any environment, while conserving oxygen and power.
- Move the patient on all ventilation modes
- Autonomous: 8 hours of independent ventilation plus hot swappable battery
- Any power source, in flight certification
- Five Preset modes: Allows clinicians to focus their attention on the patient and reduces time to make the right clinical decision

- Ease of operation
- 7" color touch screen clearly visible even outside in bright daylight or with fluorescent lighting
- All parameters and alarms displayed on one
- Intuitive user interface requires minimum training
- Curves and loops
- 72 hours of trends
- Adiustable alarms
- Downloadable event logs
- Customizable configurations